





CE
EAC



DC-250 850



1

Equipped with ZERO DUST system.
Tested and certified by TNO.

2

DC-250 1200, chassis with anti-
corrosion treatment.

3

With adjustable rule (0 to 60°)
with lateral stop.

4

Plunge effect allowing
adjustment cutting height.

DC-250 850 ZERO DUST	38 9/16" 98 cm	27 3/8x27 3/8" 69.5x69.5 cm	2 3/8 / 3 9/16" 61 / 90 mm	1 15/16" 50 mm	√	10" 250 mm	53 15/16x23 1/4x51 9/16" 137x59x131 cm	121 Lb 55 kg	154 Lb 70 kg	√	1	**1
DC-250 1200 ZERO DUST	47 7/16" 120.5 cm	33 7/16x33 7/16" 85x85 cm	2 3/8 / 3 9/16" 61 / 90 mm	1 15/16" 50 mm	√	10" 250 mm	63x32 5/16x51 9/16" 160x82x131 cm	132 Lb 60 kg	165 Lb 75 kg	√	1	**1

	REF.	54933	54934	54935	54997
DC-250 850 ZERO DUST	Voltage / RPM	230V-50Hz. / 2790	220V-60Hz. / 2790	110V-50Hz. / 2790	230V-50Hz. / 2790 + CPA SUPER PRO
DC-250 1200 ZERO DUST	REF.	55941	55942	55943	54998
	Voltage / RPM	230V-50 Hz. / 2790	220V-60 Hz. / 2790	110V-50 Hz. / 2790	230V-50 Hz. / 2790 + CPA SUPER PRO

ACCESSORIES	54999 -Laser & Level Kit DV/DC/DS/DX	54822 -Lateral Stop for DC/DS/DX	51916 -Tile Fixer DV/DC/DS/DX	54993 -Table Extension DV/DC