

## DEHUMIDIFIERS Pro Series

### Affugter specifikationer:

- Electronic control with the option to set start-stop.
- Hour counter for initiated jobs.
- Total hour counter.
- Option to set for continuous operation.
- However, does not withstand aggressive environments such as pigsties, etc.
- Easily washable removable air filter.
- Cabinet in impact-resistant plastic.
- Semi-pneumatic wheels.
- Foldable handle (70L).
- Built-in pump that lifts water 4.5m.
- 4.5m plastic hose included.
- Stackable (45L).

### Particularly suitable for:

Constructionsite, after flooding in buildings, basements, and repairs after water damage.



**70 L. DEHUMIDIFIER**

**45 L. DEHUMIDIFIER**



**STACKABLE**



| MODEL                  | 45 L.  | 70 L.  |
|------------------------|--|--|
| Staring no.            | STA-A45                                      | STA-A70                                      |
| Power Supply           | 220 - 240V / 50Hz                            |  |
| Dehumidifying Capacity | 45L/DAY (30°C RH80%)<br>25L/DAY (27°C RH60%) | 70L/DAY (30°C RH80%)<br>44L/DAY (27°C RH60%) |
| Max Power              | 460 W  | 750 W  |
| Compressor type        | Rotary                                       |  |
| Refrigerant            | R290   |  |
| Working temperature    | 5 - 35°C                                     |  |
| Air Volume             | 300 m³/h                                     | 410 m³/h                                     |
| Net Weight             | 25 kg  | 40 kg  |
| Size                   | 605 x 360 x 470 mm                           | 540 x 530 x 845 mm                           |
| Room Size Capacity     | 115 m²                                       | 180 m²                                       |

