

AFFUGTERE | IMPACT-RESISTANT PLASTIC

Pro Series

Dehumidifier specifications:

- Electronic control with the option to set start and stop.
- Hour meter for the beginning of a job.
- Total hour meter.
- Option to set for continuous operation.
- However, it does not withstand aggressive environments such as pigsties, etc.
- Easily washable detachable air filter.
- Cabinet in impact-resistant plastic.
- Semi-pneumatic wheels.
- Built-in pump that lifts water 4.5m.
- 4.5m plastic hose included.
- Option to set operation based on humidity.
- Easy-to-clean air filter.
- Quick automatic defrosting.
- Built-in pump that pumps water 4.5m vertically.

Particularly suitable for:

Construction, after flooding in buildings, basements, and repairs after water damage.



50 L. DEHUMIDIFIER
50L0950CH-PRO



65 L. DEHUMIDIFIER
65L1200CH-PRO



80 L. DEHUMIDIFIER
80L1400CH-PRO

MODEL	50L	65L	80L
Staring varenr.	50L0950CH-PRO	65L1200CH-PRO	80L1400CH-PRO
Power Supply	220 - 240V / 50Hz		
Dehumidifying Capacity	50L/DAG (30°C RH80%) 31L/DAG (27°C RH60%)	70L/DAG (30°C RH80%) 44L/DAG (27°C RH60%)	90L/DAG (30°C RH80%) 56L/DAG (27°C RH60%)
Max Power	650 W	785 W	940 W
Compressor type	Rotary		
Refrigerant	R290 / 0,15 kg	R290 / 0,26 kg	R290 / 0,29 kg
Working temperature	5 - 35°C		
Air Volume	350 m³/h	400 m³/h	580 m³/h
Net Weight	38,0 kg	44,5 kg	44,0 kg
Size	560 x 500 x 670 mm	540 x 530 x 890 mm	555 x 480 x 6820 mm
Room Size Capacity	120 m²	160 m²	330 m²

