

**AFFUGTERE | IMPACT-RESISTANT PLASTIC**

# Pro Series

**Dehumidifier specifications:**

- Electronic control with the option to set start and stop.
- Hour meter for the beginning of a job.
- Total hour meter.
- Option to set for continuous operation.
- However, it does not withstand aggressive environments such as pigsties, etc.
- Easily washable detachable air filter.
- Cabinet in impact-resistant plastic.
- Semi-pneumatic wheels.
- Built-in pump that lifts water 4.5m.
- 4.5m plastic hose included.
- Option to set operation based on humidity.
- Easy-to-clean air filter.
- Quick automatic defrosting.
- Built-in pump that pumps water 4.5m vertically.



**85 L. DEHUMIDIFIER**  
80L1400CH-PRO



**50 L. DEHUMIDIFIER**  
50L0950CH-PRO



**65 L. DEHUMIDIFIER**  
65L1200CH-PRO

**Particularly suitable for:**

Construction, after flooding in buildings, basements, and repairs after water damage.

MODEL	50L	65L	85L
<b>Staring varenr.</b>	50L0950CH-PRO	65L1200CH-PRO	80L1400CH-PRO
<b>Power Supply</b>	220 - 240V / 50Hz		
<b>Dehumidifying Capacity</b>	50L/DAG (30°C RH80%) 30L/DAG (27°C RH60%)	65L/DAG (30°C RH80%) 37L/DAG (27°C RH60%)	85L/DAG (30°C RH80%) 42L/DAG (27°C RH60%)
<b>Max Power</b>	600 W	750 W	990 W
<b>Compressor type</b>	Rotary		
<b>Refrigerant</b>	R290		
<b>Working temperature</b>	5 - 35°C		
<b>Air Volume</b>	350 m <sup>3</sup> /h	400 m <sup>3</sup> /h	580 m <sup>3</sup> /h
<b>Net Weight</b>	39 kg	44 kg	73 kg
<b>Size</b>	545 x 500 x 638 mm	810 x 500 x 490 mm	1010 x 610 x 600 mm
<b>Room Size Capacity</b>	120 m <sup>2</sup>	160 m <sup>2</sup>	330 m <sup>2</sup>

