

DEHUMIDIFIERS | **STEEL CABINET**

# S Pro Series

**Dehumidifier specifications:**

- Electronic control with the option to set start and stop.
- Hour counter for the initiated job.
- Total hour counter.
- Option for continuous operation setting.
- Not suitable for aggressive environments such as pigsties.
- Easily removable air filter.
- Steel cabinet.
- Semi-pneumatic wheels.
- Collapsible handle.
- Built-in pump that lifts water 4.5m.
- 4.5m plastic hose included.

**Example of use:**

- Construction
- Repairs after water damage
- After flooding in buildings, basements, etc.



**90 L. DEHUMIDIFIER**  
STA-A90S



**70 L. DEHUMIDIFIER**  
STA-A70S



**50 L. DEHUMIDIFIER**  
STA-A50S

MODEL	S 50 L.	S 70 L.	S 90 L.
Staring no.	STA-A50S	STA-A70S	STA-A90S
Power Supply	220 - 240V / 50Hz		
Dehumidifying Capacity	50L/DAY (30°C RH80%) 28L/DAY (27°C RH60%)	70L/DAY (30°C RH80%) 44L/DAY (27°C RH60%)	90L/DAY (30°C RH80%) 46L/DAY (27°C RH60%)
Max Power	500 W	820 W	980 W
Compressor type	Rotary		
Refrigerant	R290		
Working temperature	5 - 35°C		
Air Volume	350 m³/h	410 m³/h	500 m³/h
Net Weight	37,5 kg	38,5 kg	41 kg
Size	550 x 490 x 700 mm	555 x 480 x 820 mm	555 x 480 x 820 mm
Room Size Capacity	120 m²	160 m²	330 m²

