

DEHUMIDIFIERS S-Series

Professional, reliable dehumidifier supplied with a container and hose. Collected water can be stored in a convenient 7-liter container or drained directly into a drain using the included drainage hose.

The dehumidifier can be set to start and stop automatically at the specified humidity level.

Features:

- Electronic control with the option to set start and stop times.
- Timer for limited-time operation.
- Option to set operation based on humidity.
- Automatic defrost function.
- However, it is not suitable for use in aggressive environments such as pigsties, etc.
- Easily washable removable air filter.
- Steel casing.
- Foldable handle.
- 7-liter container for water collection.
- Option to connect a hose for direct drainage into a drain.



7 L. CONTAINER (Only for 30L. og 50L.)



DISPLAY



Example of use:

- Construction
- After flooding in buildings, basements, etc.
- Repairs after water damage.

MODEL	STA-AU 30 L.	STA-AU 50 L	STA-AU 70 L
Staring no.	STA-AU30S	STA-AU50S	STA-AU70S
Power Supply	220 - 240V / 50Hz		
Dehumidifying Capacity	30L/DAY (30°C RH80%) 20L/DAY (27°C RH60%)	50L/DAY (30°C RH80%) 30L/DAY (27°C RH60%)	70L/DAY (30°C RH80%) 40L/DAY (27°C RH60%)
Max Power	420 W	700 W	950 W
Compressor type	Rotary		
Refrigerant	R290		
Working temperature	5 - 35°C		
Air Volume (m ³ /h)	300	300	400
Weight (kg)	29	30	40
Size (mm)	480 x 450 x 655	480 x 450 x 655	615 x 535 x 1055
Room Size Capacity	0-60 m ²	50-120 m ²	100-160 m ²

