

**STARING**  
**DEHUMIDIFIERS //**

**DEHUMIDIFIERS SEMIPRO**  
**DYD-Series**

**Dehumidifier Specifications:**

- Electronic control with the option to set start/stop
- High performance
- Simple operation
- Capable of continuous operation, even in harsh environments
- Fast automatic defrosting
- Equipped with transport wheels
- Tank capacity up to 6.3 L
- Option for hose attachment

**Highly suitable for:**

Construction sites, post-flood building recovery, basements, and water damage repairs.



**12 L. DEHUMIDIFIER**  
12L0430CH



**25 L. DEHUMIDIFIER**  
25L0430CH



**50 L. DEHUMIDIFIER**  
50L0430CH

MODEL	12 L	25 L	50 L
<b>Product no.</b>	12L0430CH	25L0430CH	50L0430CH
<b>Voltage Volts</b>	220 - 240V / 50Hz		
<b>Capacity</b>	12L/DAY (30°C RH80%) 8L/DAY (27°C RH60%)	25L/DAY (30°C RH80%) 15L/DAY (27°C RH60%)	50L/DAY (30°C RH80%) 30L/DAY (27°C RH60%)
<b>Max Power</b>	170 W		
<b>Tank size</b>	2,6 L		
<b>Work temperature</b>	5 - 35°C		
<b>Air max.</b>	100 m³/h	160 m³/h	360 m³/h
<b>Weight</b>	12 kg		
<b>Size</b>	360 x 234 x 569 mm	360 x 234 x 569 mm	407 x 286 x 618 mm
<b>For roomsize up to</b>	30 m²		
<b>Noise level</b>	41 dB		
	44 dB		
	50 dB		

