



**PREMIUM**



**SLAB CUTTER G3 SUPPLEMENT GUIDE**

- Extruded aluminium guide with extra 112 cm.
- Includes two suction cups integrated into the guide.

|   | REF.  |   |
|---|-------|---|
| <b>SLAB CUTTER G3 SUPPLEMENT GUIDE AND SUCTION CUPS</b> | 16908 | 1 |

**PREMIUM**



**22MM SCORING WHEEL PLUS EXTREME (Ø 7/8") SLAB CUTTER**

- For sharp cuttings in hard tiles with rough or structured surfaces.
- Tungsten Carbide scoring wheel with a superficial Titanium treatment.
- Mounted on bearing. Enhanced smooth user preception.
- Extra-long life.

|   | REF.  |   |
|---|-------|---|
| <b>22MM SCORING WHEEL PLUS EXTREME (Ø 7/8") SLAB CUTTER</b> | 01901 | 5 |

**SUPERPRO**



**TC-125 G2 CIRCULAR CUTTER**

- Accessory exclusively for users of the SLIM CUTTER G2 manual cutting system.
- Requires the use of the SLIM CUTTER G2 guides.
- Equipped with a carbon steel slide on adjustable double set stainless steel radial bearings.
- Double dust reduction/control system. Dry and wet cutting.
- Height-adjustable cutting head (saw effect), hinged from 0° to 45°. (mitre). Fast adjustment system.
- More ergonomic. Additional bi-material handle, mainly for mitre cuts.
- Includes Ø125 blade and carrying case.

|                      | REF.  |   |                  | RPM   | W      |                |                      |                         |                        |                 |                                       |                |   |  |  |
|----------------------|-------|---|------------------|-------|--------|----------------|----------------------|-------------------------|------------------------|-----------------|---------------------------------------|----------------|---|--|--|
| <b>TC-125 G2</b>     | 51951 | √ | 220-240V 50-60Hz | 13800 | 1250 W | 126"<br>320 cm | 13/16-1"<br>20-25 mm | 9/16-11/16"<br>14-18 mm | 4 1/2-5"<br>115-125 mm | 7/8"<br>22.2 mm | 14 3/16x9 5/8x8 1/4"<br>36x24.5x21 cm | 31 Lb<br>14 kg | 1 |  |  |
| <b>TC-125 G2 UK</b>  | 51967 |   |                  |       |        |                |                      |                         |                        |                 |                                       |                |   |  |  |
| <b>TC-125 G2 USA</b> | 51987 |   | 110-130V 50-60Hz |       |        |                |                      |                         |                        |                 |                                       |                |   |  |  |